

# MATERIAL SAFETY DATA SHEET



**Biomerics, LLC**  
**Product Safety & Regulatory Affairs**  
**2700 South 900 West**  
**Salt Lake City, UT 84119**  
**USA**

**TRANSPORTATION EMERGENCY**  
CALL CHEMTREC: (800) 424-9300  
INTERNATIONAL: (703) 527-3887

**NON-TRANSPORTATION**  
Emergency Phone: Call Chemtrec  
Information Phone: (888)-874-7787

## 1. Product and Company Identification

**Product Name:** Quadrathane™ ARC  
**Material Numbers:** QTHAN-ARC-75A-000, QTHAN-ARC-80A-000, QTHAN-ARC-85A-000,  
QTHAN-ARC-90A-000, QTHAN-ARC-93A-000, QTHAN-ARC-95A-000,  
QTHAN-ARC-55D-000, QTHAN-ARC-65D-000, QTHAN-ARC-72D-000  
**Chemical Family:** Aromatic thermoplastic polyurethane  
**Chemical Name:** Polyurethane elastomer

## 2. Hazards Identification

### Emergency Overview

**Caution:**            **Color:**    Colorless to yellow    **Form:**            Solid            **Odor:**            Mild

This Material has no known health hazards.

See Section 11 for complete health hazard information.

## 3. Composition/Information on Ingredients

### **Hazardous components**

This material has no known hazards under applicable laws.

## 4. First aid measures

### **Eye contact**

In case of contact, flush eyes with plenty of lukewarm water. Get medical attention if irritation develops.

### **Skin contact**

Get medical attention if thermal burn occurs.

### **Inhalation**

If inhaled, remove to fresh air.

### **Ingestion**

Get medical attention.

### **Notes to physician**

In the event of possible diisocyanate exposure: Eyes: Stain for evidence of corneal injury. If cornea is burned, instill antibiotic/steroid preparation as needed. Workplace vapors could produce reversible corneal epithelial edema impairing vision. Skin: Treat symptomatically as for thermal burn. Ingestion: Treat symptomatically. Inhalation: Treatment is essentially symptomatic. An individual having a pulmonary sensitization reaction to this material should be removed from further exposure to any diisocyanate.

## 5. Fire-fighting measures

**Suitable extinguishing media:** Water, Foam, Dry chemical

### Special Fire Fighting Procedures

Firefighters should be equipped with self-contained breathing apparatus to protect against potentially toxic and irritating fumes.

### Unusual Fire/Explosion Hazards

Toxic and irritating gases/fumes may be given off during burning or thermal decomposition. Solid does not readily release flammable vapors.

## 6. Accidental release measures

### Spill and Leak Procedures

Pick up free solid for recycle and/ or disposal.

If molten, allow material to cool and place into an appropriate marked container for disposal.

## 7. Handling and storage

### Storage temperature:

**maximum:** 30 °C (86 °F)

### Storage period

Not Established

### Handling/Storage Precautions

Handle in accordance with good industrial hygiene and safety practices. Wash thoroughly after handling. Avoid breathing dust. Containers should be kept tightly closed to prevent contamination. Material is hygroscopic and may absorb small amounts of atmospheric moisture. Store in well ventilated place. Use good housekeeping measures to prevent dust accumulations.

### Handling Procedures

Loading and unloading may cause nuisance dust to form. Conduct any operations emitting fumes or vapors (including heat joining, cutting and or sealing of articles and clean up) under well ventilated conditions. Avoid breathing process vapors. Do not hold product for extended periods of time at elevated temperatures or allow thick masses of hot polymer to accumulate because they can decompose emitting hazardous gasses. Do not taste, swallow, or chew products. Wash thoroughly after processing. Do not store or consume food in processing areas. Fume condensates may include hazardous contaminants from additives. Condensate may be combustible and should be periodically removed from exhaust hoods, ductwork, and other surfaces. Impervious gloves should be worn during cleanup operations to prevent skin contact. Post thermal processing activities necessary to produce molded articles (such as cutting, sanding, sawing, grinding, drilling, or regrinding) may create dust or "fines". Powders, dust, and/ or fines may pose a dust explosion hazard. Electrostatic buildup may occur when pouring or transferring this product from its container. The spark produced may be sufficient to ignite vapors of flammable liquids. Always transfer product by means which void static buildup. Avoid pouring product directly from its container into combustible or flammable solvent. The major off-gasses from normal melt processing are expected to be water vapor and carbon dioxide. Other trace volatile organic components may also be emitted. Wash thoroughly after handling.

### Further Info on Storage Conditions

Protect equipment (e.g. storage bins, conveyors, dust collectors) with explosion vents.

## 8. Exposure controls/personal protection

### Industrial Hygiene/Ventilation Measures

During normal processing, use general dilution and local exhaust as necessary to control airborne vapors, mists, dusts and thermal decomposition products below appropriate airborne concentration standards/guidelines. Special ventilation and personal protective equipment (PPE) is required to control exposure to potentially harmful decomposition products whenever a TPU is heated to temperatures above its decomposition temperature. Examples would include hot knife cutting, grinding, or sawing.

### Respiratory protection

In the absence of sufficient general dilution or local exhaust ventilation a NIOSH approved air-supplied respirator may be needed during die cleaning, high temperature processing, purging or when thermal decomposition is suspected.

### Hand protection

Wear heat resistant gloves when handling molten material.

### Eye protection

Safety glasses with side-shields

### Skin and body protection

No special skin protection requirements during normal handling and use.

### Additional Protective Measures

Employees should wash their hands and face before eating, drinking, or using tobacco products. Educate and train employees in the safe use and handling of this product.

## 9. Physical and chemical properties

<b>Form:</b>	Solid
<b>Appearance:</b>	Pellets
<b>Color:</b>	Colorless to yellow
<b>Odor:</b>	Mild
<b>pH:</b>	not determined
<b>Melting Point:</b>	not determined
<b>Flash point:</b>	not determined
<b>Lower explosion limit:</b>	not determined
<b>Upper explosion limit:</b>	not determined
<b>Specific Gravity:</b>	1.2
<b>Solubility in Water:</b>	insoluble
<b>Autoignition temperature:</b>	not determined
<b>Decomposition temperature:</b>	>230° c
<b>Softening point:</b>	not determined
<b>Bulk density:</b>	not determined



## 12. Ecological information

Ecological Data for Quadrathane™ ARC  
Additional Ecotoxicological Remarks  
No data available for this product.

## 13. Disposal considerations

**Waste Disposal Method**  
Waste disposal should be in accordance with existing federal, state and local environmental control laws.

## 14. Transport information

**Land transport (DOT)**  
Non-Regulated

**Sea transport (IMDG)**  
Non-Regulated

**Air transport (ICAO/IATA)**  
Non-Regulated

## 15. Regulatory information

### United States Federal Regulations

OSHA Hazcom Standard Rating: Non-Hazardous

US. Toxic Substances Control Act: This product is sold solely for uses subject to regulation under the Federal Food, Drug and Cosmetic Act. This Product contains one or more chemical substances not on the TSCA Inventory.

### US. EPA CERCLA Hazardous Substances (40 CFR 302):

Components  
None

**SARA Section 311/312 Hazard Categories:**  
Non-hazardous under Section 311/312

### US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A):

Components  
None

### US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required:

Components  
None

### US. EPA Resource Conservation and Recovery Act (RCRA) Composite List of Hazardous Wastes and Appendix VIII Hazardous Constituents (40 CFR 261):

Under RCRA, it is the responsibility of the person who generates a solid waste, as defined in 40 CFR 261.2, to determine if that waste is a hazardous waste.

### State Right-To-Know Information

The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections of the MSDS may also be applicable for state requirements. For details on your regulatory requirements you should contact the appropriate agency in your state.

### Massachusetts, New Jersey or Pennsylvania Right to Know Substance Lists:

<u>Weight percent</u>	<u>Components</u>	<u>CAS-No.</u>
>=1%	Polyurethane Elastomer	CAS# is a trade secret

### California Prop. 65:

To the best of our knowledge, this product does not contain any of the listed chemicals, which the state of California has found to cause cancer, birth defects or other reproductive harm.

## 16. Other information

### HMIS Rating

Health	0
Flammability	1
Physical Hazard	0

0=Minimal 1=Slight 2=Moderate 3=Serious 4=Severe

\* = Chronic Health Hazard

The method of hazard communication for Biomerics LLC is comprised of Product Labels and Material Safety Data Sheets. HMIS and NFPA ratings are provided by Biomerics LLC as a customer service.

Contact person: Product Safety & Regulatory Affairs

Telephone: 801-355-2700

**This information is furnished without warranty, express or implied. This information is believed to be accurate to the best knowledge of Biomerics LLC. The information in this MSDS relates only to the specific material designated herein. Biomerics LLC assumes no legal responsibility for use of or reliance upon the information in this MSDS.**